

## Mini Test Sealing Bags 2.5 bar (36.25 psi)

The small ones with duct.



- › extremely short design
- › extremely expandable
- › up to 1 bar (14.5 psi) counter-pressure
- › optimised handling by valve connection

Mini test sealing bags 2.5 bar can be used for testing, sealing and bypassing with repairs and maintenance work, e.g. sealing tests, channel inspection, maintenance, repair and cleaning.



### Technical data

Mini Test Sealing Bags 2.5 bar/36.25 psi	Opening	Pipe diameter mm / inch	Diameter mm / inch	Cylinder length mm / inch	Total length mm / inch	Air requirement litres / cu. ft.	Weight, approx. kg / lbs
<b>PDK 4/7</b> 1441000701	6 mm 0.2 inch	40 - 70 1.6 - 2.8	37 1.5	155 6.1	250 9.8	3.5 0.12	0.4 0.9
<b>PDK 10/15</b> 1441035400	1/2"	100 - 150 3.9 - 5.9	90 3.5	150 5.9	300* 11.8*	2 0.07	1 2.2
<b>PDK 12.5/20</b> 1441035200	1/2"	125 - 200 5 - 7.8	115 4.5	150 5.9	300* 11.8*	4.4 0.16	1.2 2.6
<b>PDK 20/30</b> 1441035300	1"	200 - 300 7.8 - 11.8	185 7.2	250 9.8	410* 16*	18 0.64	4.5 9.9

\* including valve connection

**Standard test counter-pressure  
of 10 m WC (14.5 psi).**