


Pipe Sealing Bags CR

The oil-resistant alternative to the classics.



- › good handling (length/weight)
- › very flexible applicable
- › with integrated hose as an option
- › good resistance to oil and chemicals

The Pipe Sealing Bags of chloroprene rubber (CR) are characterised by an increased resistance to chemicals (e.g. against mineral oils, heating oil etc.) compared to conventional Pipe Sealing Bags of natural rubber (NR).

These Pipe Sealing Bags CR are available with an integrated inflation hose as an option.

Further sizes can be delivered on request.



Technical data

Pipe Sealing Bags CR	Pipe diameter mm / inch	Diameter mm / inch	Cylinder length mm / inch	Total length mm / inch	Air requirement litres / cu. ft.	Weight, approx. kg / lbs
RDK 7/15 1440008100	2.5 bar (36.25 psi) 70 - 150 2.8 - 5.9	68 2.7	300 11.8	345 13.4	14 0.5	0.6 1.3
RDK 15/30 1440008000	2.5 bar (36.25 psi) 150 - 300 5.9 - 11.8	145 5.7	465 18.1	510 20	80 2.8	2.5 5.5
RDK 30/60 1440007900	2.5 bar (36.25 psi) 300 - 600 11.8 - 23.4	295 11.6	735 28.9	780 30.4	508 18	7.3 16.1
RDK 60/120 1480004800	1.5 bar (21.75 psi) 600 - 1,200 23.4 - 47.2	580 22.8	1,320 52	1,365 53.7	2,475 87.4	27 59.5

RDK 2.5 bar - Test counter-pressure 10 m WC (14.5 psi)
RDK 1.5 bar - Test counter-pressure 5 m WC (7.25 psi)