


## Pipe Sealing Bags

The classics.



- › wide product range
- › only 3 sizes from 100 - 1,000 mm
- › very flexible due to the material
- › easy handling, because lightweight and short

Vetter Pipe Sealing bags are the optimum solution when quick and reliable sealing of drainage is required. A big advantage of the sealing bags are their freely selectable contact pressure (on the pipe wall): from 0.5 bar to 2.5 bar/7.25 psi to 36.25 psi.

The areas of operation are, among others:

- › sealing off sewer pipelines during repair or maintenance work
- › avoiding sewage backflow at the source location during pipe bursts, flooding, sewer inspection, sewer cleaning, repair and maintenance work

Due to the numerous application possibilities, sealing bags are used in different branches of industry, such as road construction and civil engineering companies, sewer constructors, water authorities and industry.

Vetter Pipe Sealing bags can be used for the sealing test according to DIN EN 1610.



## Technical data

Pipe Sealing Bags		Pipe diameter mm / inch	Diameter mm / inch	Cylinder length mm / inch	Total length mm / inch	Air requirement, approx. litres / cu. ft.	Weight, approx. kg / lbs
<b>RDK 2.5/4</b> 1440000101	<b>2.5 bar</b> (36.25 psi)	25 - 40 0.98 - 1.6	21 0.9	115 4.5	175 7	0.7 0.02	0.15 0.33
<b>RDK 4/7</b> 1440000201	<b>2.5 bar</b> (36.25 psi)	40 - 70 1.6 - 2.8	37 1.5	155 6.1	215 8.5	2.5 0.09	0.2 0.44
<b>RDK 7/15</b> 1440000301	<b>2.5 bar</b> (36.25 psi)	70 - 150 2.8 - 5.9	68 2.7	300 12	345 13.6	13.3 0.47	0.5 1.1
<b>RDK 10/20</b> 1440011700	<b>2.5 bar</b> (36.25 psi)	100 - 200 3.9 - 7.8	90 3.5	510 20	555 21.9	40.3 1.4	1.2 2.7
<b>RDK 15/30</b> 1440000601	<b>2.5 bar</b> (36.25 psi)	150 - 300 5.9 - 11.8	145 5.7	460 18.1	505 20	87.5 3.1	1.9 4.2
<b>RDK 20/40</b> 1440020100	<b>2.5 bar</b> (36.25 psi)	200 - 400 7.8 - 16	195 7.7	650 25.6	700 27.3	224 7.9	2.8 6.2
<b>RDK 20/50</b> 1440016700	<b>2.5 bar</b> (36.25 psi)	200 - 500 7.8 - 20	195 7.7	750 29.3	795 31	329.0 11.6	5 11
<b>RDK 30/60</b> 1440000801	<b>2.5 bar</b> (36.25 psi)	300 - 600 11.8 - 23.4	295 11.6	735 28.9	780 30.7	507.5 17.9	7 15.4
<b>RDK 50/80</b> 1440020000	<b>2.5 bar</b> (36.25 psi)	500 - 800 20 - 31.5	450 17.7	1,110 43.7	1,155 45.6	2,135 75.4	17 37.5
<b>RDK 60/100</b> 1440011900	<b>2.5 bar</b> (36.25 psi)	600 - 1,000 23.4 - 39.4	580 22.8	1,320 52	1,365 53.7	3,465 122.3	25 55
<b>RDK 50/100</b> 1480000801	<b>1.5 bar</b> (21.75 psi)	500 - 1,000 20 - 39.4	450 17.7	1,110 43.7	1,155 45.6	1,525 53.8	17 37.5
<b>RDK 60/120</b> 1480001901	<b>1.5 bar</b> (21.75 psi)	600 - 1,200 23.4 - 47.2	580 22.8	1,320 52	1,365 53.7	2,475 87.4	25 55
<b>RDK 80/140</b> 1480006000	<b>1.5 bar</b> (21.75 psi)	800 - 1,400 31.5 - 55.1	785 30.9	1,810 71.3	1,855 73	3,125 110.3	41 90.4
<b>RDK 140/170</b> 1400000300	<b>0.5 bar</b> (7.25 psi)	1,400 - 1,700 55.1 - 67	1,350 53.2	1,900 74.8	2,150 84.7	8,700 307.1	55 121.3
<b>RDK 170/200</b> 1400000100	<b>0.5 bar</b> (7.25 psi)	1,700 - 2,000 67 - 78.7	1,620 63.8	1,900 74.8	2,300 90.6	9,000 317.7	59 130.1

**RDK 2.5 bar - Test counter-pressure 10 m WC (14.5 psi)**

**RDK 1.5 bar - Test counter-pressure 5 m WC (7.25 psi)**

**RDK 0.5 bar - Test counter-pressure 2 m WC (2.9 psi)**

**Note: As an oil-resistant alternative the Pipe Sealing Bags are also available as a CR-version. You will find the Pipe Sealing Bags CR on page 16.**