


Mini Test Sealing Bags 2.5 bar (36.25 psi)

The small ones with duct.



- › extremely short design
- › extremely expandable
- › up to 1 bar (14.5 psi) counter-pressure
- › optimised handling by valve connection

Mini test sealing bags 2.5 bar can be used for testing, sealing and bypassing with repairs and maintenance work, e.g. sealing tests, channel inspection, maintenance, repair and cleaning.



Technical Data

| Mini Pipe Sealing Bags 2.5 bar/36.25 psi | Opening | Pipe diameter mm / inch | Diameter mm / inch | Cylinder length mm / inch | Total length mm / inch | Air requirement litres / cu.ft. | Weight, approx. kg / lbs |
|--|-----------------------|-------------------------|--------------------|---------------------------|------------------------|---------------------------------|--------------------------|
| PDK 4/7 1441000701 | 2 x 4 mm 2 x 0.16" | 40 - 70 1.6 - 2.8 | 37 1.5 | 155 6.1 | 250 9.8 | 3,5 0.12 | 0,4 0.9 |
| PDK 7/10 1441043900 | 1/2" | 70 - 100 2.7 - 4.0 | 68 2.7 | 190 7.5 | 340 13.4 | 6,0 0.21 | 0,4 0.88 |
| PDK 10/15 1441035400 | 1/2" | 100 - 150 4 - 6 | 90 3.5 | 150 5.9 | 300* 11.8* | 2 0.07 | 1 2.2 |
| PDK 12,5/20 1441035200 | 1/2" | 125 - 200 5 - 8 | 115 4.5 | 150 5.9 | 300* 11.8* | 4,4 0.16 | 1,2 2.6 |
| PDK 20/30 1441035300 | 1" | 200 - 300 8 - 12 | 185 7.2 | 250 9.8 | 410* 16* | 18 0.64 | 4,5 9.9 |

* including valve connection

Standard test counter-pressure of 10 m WC (14.5 psi).

Round profile