

Flange drain bag

Perfect fit for safe drainage at flanges.

- > Completely covers the flange > For DN 50 (50 mm / 1.9 inch) to DN 100 (100 mm / 3.9 inch) pipes
- > For lots of pipe connections > Sealing pressure of 1 bar (14.5 psi)

Problems with leaky pipe connections? Make the task of sealing difficult leaks on all types of flanges easier for your team. Flanges are critical pipe sections and conventional sealing bags will rarely be effective here. Vetter flange drain bags cover the flange and pipe, reliably stop the leakage of hazardous liquids and at the same time allow you to drain off the liquid in a controlled and safe manner. The bags come in three sizes to cover all customary pipelines and flanges. Gel plates are included for convenient smoothing out of minor irregularities and unevenness on the pipe's surface. It couldn't be simpler: Place the bag around the flange and pipe, close the zip fastener along the entire length of the bag and inflate the sleeves. Immediately, everything is sealed and you can commence with controlled drainage of the liquid.



Leak on pipe flange

Technical data*

Flange drain bags	External size Ø cm / Ø inch	Length cm / inch	Air requirement at 1.5 bar (21.75 psi) litres / cu. ft.	Weight of individual bag, approx. kg / lbs	Weight of set, approx. kg / lbs
DN 50 1500006600	21 8.3	90 35	1.25 0.1	3.1 6.8	178 39.2
DN 80 1500019200	21 8.3	90 35	1.25 0.1	3.1 6.8	178 39.2
DN 100 1500023400	25 9.8	92 36	1.25 0.1	3.5 7.7	18.4 40.1

**Uniform sealing pressure of
10 m WC (14.5 psi).**

Flange drain bags:
Working pressure: 1.5 bar (21.75 psi)
Test pressure: 1.95 bar (28.5 psi)

*Technical changes reserved

All sets described here include as standard components:

- > Inflation hose 1.5 bar, 10 m, blue (21.75 psi, 32 ft.)
- > Acid drain hose, 5 m (16.4 ft.), with D suction coupling V4A
- > Transport case 800x600 x 120 mm (32 x 24 x 4.7 inch)
- > Foot pump with safety valve 1.5 bar (21.75 psi)

Flange drain bag sets

DN 50 **1500019600**

Flange drain bag DN 50, 1.5 bar (21.75 psi)
and 4 sealing gel plates

DN 80 **1500019900**

Flange drain bag DN 80, 1.5 bar (21.75 psi)
and 4 sealing gel plates

DN 100 **1500023700**

Flange drain bag DN 100, 1.5 bar (21.75 psi)
and 6 sealing gel plates



Flange drain bag set



In operation ...

- > Sealing and controlled drainage of hazardous substances
- > On flanges and pipe connections



Good reasons:

- > Gas- and liquid-tight zip fastener
- > Acid drain hose with shut-off unit
- > Gel plates supplied to smooth out unevenness included



Guaranteed quality:

- > Individually tested (with inspection seal)
- > Stainless steel connections

