

Mini leak sealing bags

The small and quick leak-stoppers.

- > Quickly attached with Velcro belt
- > Up to 1.4 bar (20.3 psi) counterpressure
- > Delivered in practical case
- > For containers with diameters 10 – 90 cm (4 – 35 inch)

Velcro mini leak sealing bags are ideal for leaks in small containers with a diameter between 10 and 90 cm (4 and 35 inch). The mini leak sealing bags securely seal liquids and gases, are easy to attach and provide a quick solution in emergencies. The maximum working pressure of 1.5 bar (21.75 psi) is soon reached with just a few strokes of the foot pump – and the container is sealed. Quick and safe Velcro fasteners on the metal-free tension belts make light work of attaching the sealing bags – even in difficult positions.



Mini leak sealing bag with practical Velcro tension belts for quick and easy attachment.

Mini leak sealing bags set

1500009400



Mini leak sealing bags type LDK 10/10, 10/10/25, 20/20

Foot pump with safety valve 1.5 bar (21.75 psi)

2 tension belts, 150 cm (59 inch) and 3 tension belts, 300 cm (117 inch), blue

Transport case 600x400x183 mm (24 x 16 x 7 inch)

Technical data*

Mini leak sealing bags	Size (L x W x H) cm / inch	Sealing area cm ² / inch ²	Air requirement at 1.5 bar (21.75 psi) litres / cu. ft.	Weight of individual bag, approx. kg / lbs
LDK 10/10 1500008300	15 x 15 x 1.2** 6 x 6 x 0.5	9.5 x 9.5 3.7 x 3.7	0.8 0.03	0.5 1.1
LDK 10/25 1500008500	15 x 31 x 1.2** 6 x 12 x 0.5	9.5 x 25.5 3.7 x 10	1.3 0.05	0.8 1.8
LDK 20/20 1500008600	25 x 25 x 1.2** 10 x 10 x 0.5	19.5 x 19.5 7.7 x 7.7	5.0 0.18	1.1 2.4

Uniform sealing pressure of 14 m WC (20.3 psi).

Mini leak sealing bags:
Working pressure: 1.5 bar (21.75 psi) 10.4 kg (23 lbs)
Test pressure: 1.95 bar (28.5 psi)



In operation...

- > Small containers
- > Pipes
- > Rolling hoop drums
- > Containers with diameters 10 – 90 cm (4 – 35 inch)



Good reasons:

- > Flat design (1.2 cm / 0.5 inch)
- > Low air requirement
- > Can be inflated with a foot pump



Guaranteed quality:

- > Individually tested (with inspection seal)
- > Good resistance to chemicals

