


Mini pipe sealing bags

The small flexible ones



- › Extremely short design
- › Maintains counterpressure up to 1 bar (14.5 psi)
- › Very high expansion
- › Simple handling

With their short design, mini pipe sealing bags are particularly suitable for sealing building connection lines. In addition, they are always used when flexibility or the ability to negotiate bends is required. This is frequently the case for the HVAC and plumbing sector as well as for oil and gasoline separation tests according to DIN 1999 T 100. Here you are always optimally equipped with Vetter's extensive range of mini pipe sealing bags. Also available with tire valve.

Also available with tire valve



With rounded tip:

RDK 8/15

(Item number 1440018800)

RDK 15/20

(Item number 1440018900)

Technical data

Standard test counter-pressure of 10 mWC (14.5 psi)

Mini pipe sealing bags <i>2.5 bar/36.25 psi</i>	Pipe diameter <i>mm/inch</i>	Diameter <i>mm/inch</i>	Cylinder length <i>mm/inch</i>	Total length <i>mm/inch</i>	Air requirement <i>litre/cu. ft.</i>	Weight approx. <i>kg/lbs</i>
RDK 2,5/4 1440000101	25–40 1–1.6	21 0.9	115 4.5	175 7.0	0.7 0.02	0.15 0.33
RDK 4/7 1440000201	40–70 1.6–2.8	37 1.5	155 6.1	215 8.5	2.5 0.09	0.2 0.44
RDK 7/10 1440025900	70–100 2.8–4.0	68 2.7	130 5.1	175 7.0	6 0.21	0.4 0.88
RDK 8/15 1440018800	80–150 3.1–6	72 2.8	120 4.7	170 7.0	11 0.39	0.4 0.88
RDK 10/15 1440010500	100–150 4–6	89 3.5	130 5.1	175 7.0	7 0.25	0.56 1.23
RDK 12,5/20 1440010700	125–200 5–8	115 4.5	150 5.9	195 7.7	30 1.06	0.76 1.68
RDK 15/20 1440018900	150–200 6–8	90 3.5	150 5.9	195 7.7	13 0.46	0.6 1.32
RDK 15/30 1440010600	150–300 6–12	145 5.7	200 8.0	245 9.7	54 1.91	1.73 3.81